


SQTP2.5P4-8W

Terminal Type -SQTP2.5P4-8W , Mini and Micro Terminal block, nominal voltage: 800 V, nominal current: 24 A , connection method: Spring Cage Connection, number of connections: 32, Rated cross section: 2.5 mm² , cross-section: 0.08 mm² – 4 mm², AWG: 24-12 , mounting type: Panel Mounted



Approvals



General Information

Product Name	SQTP2.5P4-8W
Connection Method	Spring Cage Connection
Rating	800 V/24 A/2.5 mm ² /NAP Nm
HSN Number	8904476701459
Standard Packing Qty(in No)	5
Country Of Origin	India
Screw thread	NAP

Dimensions & Weight

Width	95.8 mm	3.77 inch
Length	32 mm	1.26 inch
Height	22 mm	0.87 inch
Weight of std. Packing Unit	0.4 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	

Rated Conductor Size

Conductor cross section flexible min	0.08 mm ²
Conductor cross section flexible max	2.5 mm ²
Conductor cross section solid min	0.08 mm ²
Conductor cross section solid max	4 mm ²

Ratings - IEC

Connection in acc. with standard	IEC60947-7-1
Nominal Voltage U_n	800 V
Nominal Current I_n	24 A
Nominal cross section	2.5 mm ²
Short-time current	0.3 kA
Rated surge voltage	8 kV
Degree of pollution	3

