


TGQ2.5-2T

Terminal Type - TGQ2.5-2T, Multi-level Ground modular terminal block, connection method: Screw connection, number of connections: 4, cross section: 0.14 mm² - 4 mm², Rated cross-section: 2.5 mm², mounting type: TS 35/7.5, TS 35/15



Approvals



General Information

Product Name	TGQ2.5-2T
Connection Method	Screw Connection
Rating	NAP V/NAP A/2.5 mm ² /0.4 Nm
HSN Number	8904476701671
Standard Packing Qty(in No)	100
Country Of Origin	India
Screw thread	M2.6

Dimensions & Weight

Width	5 mm	0.2 inch
Length	70.69 mm	2.78 inch
Height	0 mm	2.46 inch
Weight of std. Packing Unit	2.2 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Green-Yellow
Colour Variants	

Rated Conductor Size

Conductor cross section flexible min	0.14 mm ²
Conductor cross section flexible max	2.5 mm ²
Conductor cross section solid min	0.14 mm ²
Conductor cross section solid max	4 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-2
Nominal Voltage U_n	NAP V
Nominal Current I_n	NAP A
Nominal cross section	2.5 mm ²
Short-time current	0.3 kA
Rated surge voltage	NAP kV
Degree of pollution	3

Ratings - ATEX

ATEX Standard	EN 60079-7
ATEX Nominal Voltage U_n	V
ATEX Nominal Current I_n	A
ATEX Cross Sec. Flexible Max.	2.5 mm ²

Ratings - CSA

CSA Standard	
B - CSA Nominal Voltage U_N	V
B - CSA Nominal Current I_N	A
B - CSA Wire Min	AWG
B - CSA Wire Max	AWG

Ratings - UL

UL Standard	UL 1059
B - UL Nominal Voltage U_N	V
B - UL Nominal Current I_N	A
B - UL Wire Min	24 AWG
B - UL Wire Max	12 AWG