


OAT10DTS

Terminal Type - OAT10DTS, Test Disconnect terminal block, nominal voltage: 1000 V, nominal current: 57 A, Rated cross-section - 10 mm² connection method: Bolt connection, number of connections: 2, cross-section: 0.5 mm² - 10 mm², mounting type: TS 35/7.5, TS 35/15, TS 32



Approvals

CB CE

General Information

Product Name	OAT10DTS
Connection Method	Bolt Connection
Rating	1000 V/57 A/10 mm ² /2 Nm
HSN Number	85389000
Standard Packing Qty(in No)	50
Country Of Origin	India
Screw thread	M5

Dimensions & Weight

Width	13 mm	0.51 inch
Length	95 mm	3.74 inch
Height	63.45 mm	2.5 inch
Weight of std. Packing Unit	3.5 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khakhi ,

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	10 mm ²
Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	10 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage U_n	1000 V
Nominal Current I_n	57 A
Nominal cross section	10 mm ²
Short-time current	1.2 kA
Rated surge voltage	8 kV
Degree of pollution	3

