



TQ2.5-3T+WOE

Terminal Type -TQ2.5-3T+WOE, Multi-level terminal Block, nominal voltage: 400 V, nominal current: 24 A, Rated cross-section: 2.5 mm², connection method: Screw connection, number of connections: 6, cross-section: 0.14 mm² - 4 mm², mounting type: TS 35/7.5, TS 35/15



Approvals

CB LRCE

General Information

Product Name	TQ2.5-3T+WOE
Connection Method	Screw Connection
Rating	400 V/24 A/2.5 mm ² /0.4 Nm
HSN Number	85389000
Standard Packing Qty(in No)	50
Country Of Origin	India
Screw thread	M2.6

Dimensions & Weight

Width	6 mm	0.24 inch
Length	94.6 mm	3.72 inch
Height	71.5 mm	2.81 inch
Weight of std. Packing Unit	1.39 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khakhi ,

Rated Conductor Size

Conductor cross section flexible min	0.14 mm ²
Conductor cross section flexible max	2.5 mm ²
Conductor cross section solid min	0.14 mm ²
Conductor cross section solid max	4 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage U_n	400 V
Nominal Current I_n	24 A
Nominal cross section	2.5 mm ²
Short-time current	0.3 kA
Rated surge voltage	8 kV
Degree of pollution	3

