



TQ2.5-D

Terminal Type - TQ2.5 , Feed-through terminal block with build in diode, nominal voltage: 1000 V, Diode current: 1 A , connection method: Screw connection, number of connections: 2, , Rated cross-section: 2.5 mm² , cross section:0.14 mm - 4 mm², mounting type: TS 35/7.5, TS 35/15



Approvals



General Information

Product Name	TQ2.5-D
Connection Method	Screw Connection
Rating	1000 V/Diode Current - 1 A/2.5 mm ² /0.4 Nm
HSN Number	8904476705358
Standard Packing Qty(in No)	100
Country Of Origin	India
Screw thread	M2.6

Dimensions & Weight

Width	5 mm	0.2 inch
Length	58.55 mm	2.31 inch
Height	45.5 mm	1.79 inch
Weight of std. Packing Unit	1 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khakhi ,

Rated Conductor Size

Conductor cross section flexible min	0.14 mm ²
Conductor cross section flexible max	2.5 mm ²
Conductor cross section solid min	0.14 mm ²
Conductor cross section solid max	4 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage U_n	1000 V
Nominal Current I_n	Diode Current - 1 A
Nominal cross section	2.5 mm ²
Short-time current	0.3 kA
Rated surge voltage	8 kV
Degree of pollution	3

