


TQ2.5

Terminal Type - TQ2.5 , Feed-through terminal block, nominal voltage: 1000 V, nominal current: 24 A, Rated cross-section: 2.5 mm², connection method: Screw connection, number of connections: 2, cross section: 0.14 mm - 4 mm², AWG: 24-12 , mounting type: TS 35/7.5, TS 35/15



Approvals



General Information

Product Name	TQ2.5
Connection Method	Screw Connection
Rating	1000 V/24 A/2.5 mm ² /0.4 Nm
HSN Number	85389000
Standard Packing Qty(in No)	100
Country Of Origin	India
Screw thread	M2.6

Dimensions & Weight

Width	5 mm	0.2 inch
Length	58.55 mm	2.31 inch
Height	45.5 mm	1.79 inch
Weight of std. Packing Unit	0.78 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khakhi ,

Rated Conductor Size

Conductor cross section flexible min	0.14 mm ²
Conductor cross section flexible max	2.5 mm ²
Conductor cross section solid min	0.14 mm ²
Conductor cross section solid max	4 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage U_n	1000 V
Nominal Current I_n	24 A
Nominal cross section	2.5 mm ²
Short-time current	0.3 kA
Rated surge voltage	8 kV
Degree of pollution	3

Ratings - ATEX

ATEX Standard	
ATEX Nominal Voltage U_n	V
ATEX Nominal Current I_n	A
ATEX Cross Sec. Flexible Max.	mm ²

Ratings - CSA

CSA Standard	CSA C22.2 NO 158
B - CSA Nominal Voltage U_N	600 V
B - CSA Nominal Current I_N	25 A
B - CSA Wire Min	24 AWG
B - CSA Wire Max	12 AWG

Ratings - UL

UL Standard	UL 1059
B - UL Nominal Voltage U_N	600 V
B - UL Nominal Current I_N	25 A
B - UL Wire Min	24 AWG
B - UL Wire Max	12 AWG