# *TQF4AD24V*

Terminal Type - TQF4AD24V, Fuse terminal block, nominal voltage: 24 V, nominal current: 6.3 A, Rated cross-section: 4.0 mm², suitable size of cartridge fuse: 5X20 mm, connection method: Screw connection, number of connections: 2, cross-section: 0.14 mm² - 6 mm², AWG: 24-10, mounting type: TS 35/7.5, TS 35/15





## Approvals

CE

## General Information

| | |
|---|---|
| Product Name | TQF4AD24V |
| Connection Method | Screw Connection |
| Rating | 24 V/6.3 A/4 mm²/0.5 Nm |
| HSN Number | 8904476701756 |
| Standard Packing Qty(in No) | 100 |
| Country Of Origin | India |
| Screw thread | M3 |

## Dimensions & Weight

| | | |
|---|---|---|
| Width | 6 mm | 0.24 inch |
| Length | 58.5 mm | 2.3 inch |
| Height | 70.7 mm | 2.78 inch |
| Weight of std. Packing Unit | 1.65 Kg | |

## Material Data

| | |
|---|---|
| Insulating Material | Polyamide 6,6 |
| Standard Colour | Gray |
| Colour Variants | Red , Yellow , Blue , Black , Green , Khaki , |

## Rated Conductor Size

| | |
|---|---|
| Conductor cross section flexible min | 0.14 mm² |
| Conductor cross section flexible max | 4 mm² |
| Conductor cross section solid min | 0.14 mm² |
| Conductor cross section solid max | 6 mm² |

## Ratings - IEC

| | |
|---|---|
| Connection in acc. with standard | IEC 60947-7-1 , IEC 60947-7-3 |
| Nominal Voltage $U_n$ | 24 V |
| Nominal Current $I_n$ | 6.3 A |
| Nominal cross section | 4 $mm^2$ |
| Short-time current | NAP kA |
| Rated surge voltage | 8 kV |
| Degree of pollution | 3 |