

TQF4AD48V-2T

Terminal Type - TQF4AD48V-2T, Multi-tier terminal block with fuse in upper tier, nominal voltage: 48 V, nominal current: 6.3 A (UT), 32 A(LT), Rated cross-section – 4.0 mm², suitable size of cartridge fuse: 5X20 mm, connection method: Screw connection, number of connections: 4, cross-section: 0.14 mm² - 6 mm², mounting type: TS 35/7.5, TS 35/15





Approvals

CE

General Information

Product Name	TQF4AD48V-2T
Connection Method	Screw Connection
Rating	48 V/UT-6.3 A,LT-32 A/4 mm^2/0.5 Nm
HSN Number	8904476701800
Standard Packing Qty(in No)	50
Country Of Origin	India
Screw thread	M3

Dimensions & Weight

Width	6 mm	0.24 inch
Length	91.9 mm	3.62 inch
Height	95.9 mm	3.78 inch
Weight of std. Packing Unit	1.1 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khaki ,

Rated Conductor Size

Conductor cross section flexible min	0.14 mm^2
Conductor cross section flexible max	4 mm^2
Conductor cross section solid min	0.14 mm^2
Conductor cross section solid max	6 mm^2

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1 , IEC 60947-7-2
Nominal Voltage U_n	48 V
Nominal Current I_n	UT-6.3 A,LT-32 A
Nominal cross section	4 mm^2
Short-time current	0.48 kA
Rated surge voltage	8 kV
Degree of pollution	3