



DUTKD4TSWS

Terminal Type - DUTKD4TSWS , Knife Disconnect Terminal block with test socket screw , nominal voltage: 1000 V, nominal current: 20 A, connection method: Screw connection with spring support , number of connections: 2, Rated cross section: 4 mm², cross section: 0.5 mm² – 4 mm², mounting type: TS35/7.5 , TS35/15 and TS32



Approvals

CE

General Information

Product Name	DUTKD4TSWS
Connection Method	Screw Connection with spring support
Rating	1000 V/20 A/4 mm ² /0.6 Nm
HSN Number	85389000
Standard Packing Qty(in No)	100
Country Of Origin	India
Screw thread	M2.6

Dimensions & Weight

Width	6 mm	0.24 inch
Length	62 mm	2.44 inch
Height	56 mm	2.2 inch
Weight of std. Packing Unit	1.55 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khakhi ,

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	4 mm ²
Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	4 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage U_n	1000 V
Nominal Current I_n	20 A
Nominal cross section	4 mm ²
Short-time current	0.3 kA
Rated surge voltage	8 kV
Degree of pollution	3

